

Timber Specifications

Box frame	Hardwood
Box frame cill	Hardwood
Sashes	Hardwood
Glazing Beads and bonded glazing bars	Hardwood
Parting bead	Hardwood
Staff bead	Hardwood

Window horn details

Top sash	90mm Victorian horn
Bottom sash	90mm Victorian horn

Paint finish

Primed	Factory spray primer (<i>tekno</i>)
--------	---------------------------------------

Standard Glazing Specifications

	Standard*	HERITAGE DOUBLE GLAZED INDIVIDUAL PANES*	Single Glazed*
	18mm double glazed units	9 or 12mm double glazed units	4mm Low iron glass
Internal glass	4mm Pilkington K Glass	4mm Pilkington K Glass	
Airspace	10mm	4mm	
Gas	Argon	Argon/Krypton	
External glass	4mm Low iron	4mm Low iron	
U value Max	1.5*	1.5*	
Spacer colour	White	White	
External finish	Bonded glazing bar	Individual fronted with dry seal	

**All glazing types can be supplied toughened*

Draught Proofing

Perimeter seal	5.5mm bush pile fitted to sashes
----------------	----------------------------------

Standard Ironmongery

Axle Pulleys	Rustproof nylon wheel axle pulleys
Sash cords	6mm Pre-stretched nylon sash cord
Fasteners	Chrome or Brass
Weights	Lead sash weights